

More discrete than non-dome security cameras, mini-dome cameras are ideal for surveillance sites where cameras need to be less noticeable, such as building entrances, convenience and retail stores and shopping malls.

ICRealtime's new rugged, fixed lens mini-dome camera incorporates a 1/3 SONY sensor for outstanding picture quality (420 TVL) and excellent sensitivity (0.5 Lux). It comes standard with a 3.6 mm lens that is easily changed out for other lenses up to 12mm.



Main Features:

- 1/3" SONY CCD
- 420 TV Lines
- 0.5 Lux Minimum Illumination
- Vandal proof
- 3.6mm Fix Lens

Specifications:

- Image Sensor: 1/3" SONY Sensor CCD
- Resolution: 420 TV Lines
- Effective Pixel: 297K
- Minimum Illumination: 0.5 Lux
- S/N Ratio: > 50dB
- Signal Format: NTSC / PAL
- Lens: 3.6mm Fixed (optional 4mm, 6mm, 8mm, 12mm)
- Gain Control: Auto
- Auto Shutter (AES): NTSC/EIA: 1/60 ~ 1/20,000 sec.; PAL/CCIR: 1/50 ~ 1/100,000 sec.
- Gamma Correction: 0.45
- White Balance: Auto
- Power Supply: 12V DC
- Working Temperature: -10°C ~ +50°C (14°F ~ 122°F)
- Working Humidity: 10% - 90%
- Barometric Pressure: 86kpa - 106kpa